

FAG 23068-K-MB + AH3068G参数

尺寸	$D_{a\ max}$	502	mm	-
	d	340	mm	-
	d_{2G}	Tr360x5		-
	$d_{a\ min}$	358	mm	-
	d_s	12.5	mm	-
	l	162	mm	-
	n_s	23.5	mm	-
	$r_{a\ max}$	4	mm	-
	r_{min}	5	mm	-
说明		AH3068G		型号, 退卸套
重量	m	101000	g	质量
	m_1	18600	g	质量, 退卸套
尺寸	d_{1H}	320	mm	-
	D	520	mm	-
	B	133	mm	-
	a	9	mm	-
	b	28	mm	-
	D_1	464.6	mm	-
基本额定载荷	C_r	2360000	N	基本额定动载荷, 径向
计算系数	e	0.25		-
	Y_1	2.69		-
	Y_2	4		-
基本额定载荷	C_{0r}	4550000	N	基本额定静载荷, 径向
计算系数	Y_0	2.63		-
极限转速	n_G	1330	r/min	极限转速
参考转速	n_B	840	r/min	参考速度
疲劳极限载荷	C_{ur}	285000	N	疲劳极限载荷, 径向

FAG 23068-K-MB + AH3068G图片



参考资料:<http://www.sozhou.com/p/061a7cd1.html>