

## FAG 30318-A参数

尺寸	d	90	mm	-	
	D	190	mm	-	
	T	46.5	mm	-	
	a	37	mm	-	
	B	43	mm	-	
	C	36	mm	-	
	$C_{a \min}$	6	mm	-	
	$C_{b \min}$	10.5	mm	-	
	$D_{a \max}$	176	mm	-	
	$D_{a \min}$	165	mm	-	
	$D_{b \min}$	176	mm	-	
	$d_1$	135	mm	-	
	$d_{a \max}$	113	mm	-	
	$d_{b \min}$	104	mm	-	
	$r_{1, 2 \min}$	4	mm	-	
	$r_{3, 4 \min}$	3	mm	-	
	$r_{a \max}$	4	mm	-	
	$r_{b \max}$	3	mm	-	
	重量	m	5830	g	质量
	基本额定载荷	$C_r$	330000	N	基本额定动载荷，径向
$C_{0r}$		395000	N	基本额定静载荷，径向	
计算系数	e	0.35		-	
	Y	1.74		-	
	$Y_0$	0.96		-	
疲劳极限载荷	$C_{ur}$	43500	N	疲劳极限载荷，径向	
极限转速	$n_G$	3850	r/min	极限转速	
参考转速	$n_B$	3100	r/min	参考速度	

FAG 30318-A图片

