

FAG 30230-A参数

说明		T4GB150		根据 DIN ISO 355 的 对应型号
尺寸	$C_{b \text{ min}}$	11	mm	-
	$D_{a \text{ max}}$	256	mm	-
	$D_{a \text{ min}}$	234	mm	-
	$D_{b \text{ min}}$	250	mm	-
	d_1	201	mm	-
	$d_{a \text{ max}}$	175	mm	-
	$d_{b \text{ min}}$	164	mm	-
	$r_{1, 2 \text{ min}}$	4	mm	-
	$r_{3, 4 \text{ min}}$	3	mm	-
	$r_{a \text{ max}}$	4	mm	-
	$r_{b \text{ max}}$	3	mm	-
	重量	m	11000	g
基本额定载荷	C_r	465000	N	基本额定动载荷，径向
	C_{0r}	630000	N	基本额定静载荷，径向
计算系数	e	0.44		-
	Y	1.38		-
	Y_0	0.76		-
疲劳极限载荷	C_{ur}	74000	N	疲劳极限载荷，径向
极限转速	n_G	2650	r/min	极限转速
参考转速	n_B	1870	r/min	参考速度
尺寸	d	150	mm	-
	D	270	mm	-
	T	49	mm	-
	a	52	mm	-
	B	45	mm	-
	C	38	mm	-

FAG 30230-A图片

