

## FAG 32217-A参数

尺寸	$C_{a \min}$	5	mm	-
	$C_{b \min}$	8.5	mm	-
	$D_{a \max}$	140	mm	-
	$D_{a \min}$	130	mm	-
	$D_{b \min}$	142	mm	-
	$d_1$	114.6	mm	-
	$d_{a \max}$	96	mm	-
	$d_{b \min}$	95	mm	-
	$r_{1, 2 \min}$	2.5	mm	-
	$r_{3, 4 \min}$	2	mm	-
	$r_{a \max}$	2.5	mm	-
	$r_{b \max}$	2	mm	-
重量	m	2720	g	质量
基本额定载荷	$C_r$	226000	N	基本额定动载荷, 径向
	$C_{0r}$	305000	N	基本额定静载荷, 径向
计算系数	e	0.42		-
	Y	1.43		-
	$Y_0$	0.79		-
疲劳极限载荷	$C_{ur}$	36000	N	疲劳极限载荷, 径向
极限转速	$n_G$	4700	r/min	极限转速
参考转速	$n_B$	2900	r/min	参考速度
说明		T3EC085		根据 DIN ISO 355 的 对应型号
尺寸	d	85	mm	-
	D	150	mm	-
	T	38.5	mm	-
	a	34	mm	-
	B	36	mm	-

FAG 32217-A图片

