

FAG 23060-K-MB + H3060参数

说明		H3060		质量, 紧定套
重量	m	72200	g	质量
	m_1	23800	g	质量, 紧定套
基本额定载荷	C_r	1960000	N	基本额定动载荷, 径向
计算系数	e	0.25		-
	Y_1	2.69		-
	Y_2	4		-
基本额定载荷	C_{0r}	3650000	N	基本额定静载荷, 径向
计算系数	Y_0	2.63		-
极限转速	n_G	1550	r/min	极限转速
参考转速	n_B	980	r/min	参考速度
疲劳极限载荷	C_{ur}	223000	N	疲劳极限载荷, 径向
尺寸	d_{1H}	280	mm	-
	D	460	mm	-
	B	118	mm	-
	$B_{a \min}$	12	mm	-
	c	42	mm	-
	c_1	53	mm	-
	D_1	412.6	mm	-
	$D_{a \max}$	445.4	mm	-
	D_m	360	mm	-
	d	300	mm	-
	$d_{a \max}$	337	mm	-
	$d_{b \min}$	313	mm	-
	d_s	9.5	mm	-
	l	168	mm	-
	n_s	17.7	mm	-

$r_{a \max}$	3	mm	-
r_{\min}	4	mm	-

FAG 23060-K-MB + H3060图片

