

### FAG 23128-E1-K-TVPB参数

尺寸	d	140	mm	-
	D	225	mm	-
	B	68	mm	-
	D <sub>1</sub>	201	mm	-
	D <sub>a max</sub>	213	mm	-
	d <sub>2</sub>	157.1	mm	-
	d <sub>a min</sub>	152	mm	-
	d <sub>s</sub>	4.8	mm	-
	n <sub>s</sub>	9.5	mm	-
	r <sub>a max</sub>	2.1	mm	-
	r <sub>min</sub>	2.1	mm	-
	重量	m	9460	g
基本额定载荷	C <sub>r</sub>	760000	N	基本额定动载荷，径向
计算系数	e	0.27		-
	Y <sub>1</sub>	2.49		-
	Y <sub>2</sub>	3.71		-
基本额定载荷	C <sub>0r</sub>	1010000	N	基本额定静载荷，径向
计算系数	Y <sub>0</sub>	2.43		-
极限转速	n <sub>G</sub>	3000	r/min	极限转速
参考转速	n <sub>B</sub>	1960	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	88000	N	疲劳极限载荷，径向

### FAG 23128-E1-K-TVPB图片



参考资料:<http://www.sozhou.com/p/126a0219.html>