

FAG B71938-C-T-P4S参数

| | | | | |
|--------|----------------------|--------|-------|-------------|
| 尺寸 | d | 190 | mm | - |
| | D | 260 | mm | - |
| | B | 33 | mm | - |
| | a | 47 | mm | - |
| | D_a H12 | 247 | mm | - |
| | d_a h12 | 202 | mm | - |
| | $r_{l \text{ min}}$ | 1 | mm | - |
| | $r_{a \text{ max}}$ | 1 | mm | - |
| | $r_{al \text{ max}}$ | 1 | mm | - |
| | r_{min} | 2 | mm | - |
| 重量 | m | 4330 | g | 质量 |
| 基本额定载荷 | C_r | 174000 | N | 基本额定动载荷, 径向 |
| | C_{0r} | 152000 | N | 基本额定静载荷, 径向 |
| 系数 | f_0 | 16.4 | | - |
| 极限转速 | $n_{G \text{ Fett}}$ | 5000 | r/min | 脂润滑时的极限转速 |
| | $n_{G \text{ Öl}}$ | 7500 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | C_{ur} | 10400 | N | 疲劳极限载荷, 径向 |

FAG B71938-C-T-P4S图片



