

FAG 33110参数

尺寸	d	50	mm	-	
	D	85	mm	-	
	T	26	mm	-	
	a	21	mm	-	
	$C_{b \text{ min}}$	6	mm	-	
	$D_{a \text{ max}}$	78	mm	-	
	$D_{a \text{ min}}$	74	mm	-	
	$D_{b \text{ min}}$	82	mm	-	
	d_1	69.1	mm	-	
	$d_{a \text{ max}}$	56	mm	-	
	$d_{b \text{ min}}$	57	mm	-	
	$r_{1, 2 \text{ min}}$	1.5	mm	-	
	$r_{3, 4 \text{ min}}$	1.5	mm	-	
	$r_{a \text{ max}}$	1.5	mm	-	
	$r_{b \text{ max}}$	1.5	mm	-	
	重量	m	642	g	质量
	基本额定载荷	C_r	86000	N	基本额定动载荷，径向
C_{0r}		122000	N	基本额定静载荷，径向	
计算系数	e	0.41		-	
	Y	1.46		-	
	Y_0	0.8		-	
疲劳极限载荷	C_{ur}	15200	N	疲劳极限载荷，径向	
极限转速	n_G	8200	r/min	极限转速	
参考转速	n_B	4600	r/min	参考速度	
说明		T3CE050		根据 DIN ISO 355 的 对应型号	
尺寸	B	26	mm	-	
	C	20	mm	-	

FAG 33110图片

