

FAG 7304-B-TVP参数

| | | | | |
|--------|---------------|-------|-------|------------|
| 尺寸 | d | 20 | mm | - |
| | D | 52 | mm | - |
| | B | 15 | mm | - |
| | a | 23 | mm | - |
| | D_1 | 39.7 | mm | - |
| | $D_{a \max}$ | 45 | mm | - |
| | $D_{b \max}$ | 47.8 | mm | - |
| | d_1 | 33 | mm | - |
| | $d_{a \min}$ | 27 | mm | - |
| | $r_{1 \min}$ | 0.6 | mm | - |
| | $r_{a \max}$ | 1 | mm | - |
| | $r_{a1 \max}$ | 0.6 | mm | - |
| | r_{\min} | 1.1 | mm | - |
| | 重量 | m | 143 | g |
| 基本额定载荷 | C_r | 20400 | N | 基本额定动载荷，径向 |
| 计算系数 | e | 1.14 | | - |
| | X | 0.35 | | - |
| | Y | 0.57 | | - |
| | Y_0 | 0.26 | | - |
| 基本额定载荷 | C_{0r} | 11100 | N | 基本额定静载荷，径向 |
| 极限转速 | n_G | 17600 | r/min | 极限转速 |
| 参考转速 | n_B | 11500 | r/min | 参考速度 |
| 疲劳极限载荷 | C_{ur} | 750 | N | 疲劳极限载荷，径向 |

FAG 7304-B-TVP图片



参考资料: <http://www.sozhou.com/p/1f4576b3.html>