

## FAG 32956参数

尺寸	$D_{a \min}$	348	mm	-
	$D_{b \min}$	368	mm	-
	$d_1$	330	mm	-
	$d_{a \max}$	298	mm	-
	$d_{b \min}$	292	mm	-
	$r_{1, 2 \min}$	3	mm	-
	$r_{3, 4 \min}$	2.5	mm	-
	$r_{a \max}$	3	mm	-
	$r_{b \max}$	2.5	mm	-
重量	m	19900	g	质量
基本额定载荷	$C_r$	740000	N	基本额定动载荷，径向
	$C_{0r}$	1520000	N	基本额定静载荷，径向
计算系数	e	0.43		-
	Y	1.39		-
	$Y_0$	0.76		-
疲劳极限载荷	$C_{ur}$	162000	N	疲劳极限载荷，径向
极限转速	$n_G$	1670	r/min	极限转速
参考转速	$n_B$	940	r/min	参考速度
说明		T4EC280		根据 DIN ISO 355 的 对应型号
尺寸	d	280	mm	-
	D	380	mm	-
	T	63.5	mm	-
	a	75	mm	-
	B	63.5	mm	-
	C	48	mm	-
	$C_{a \min}$	11	mm	-
	$C_{b \min}$	15.5	mm	-

FAG 32956图片

