

FAG 23972-K-MB + AH3972G参数

尺寸	$d_{1H}$	340	mm	-
	D	480	mm	-
	B	90	mm	-
	a	7	mm	-
	b	21	mm	-
	$D_1$	447.1	mm	-
	$D_{a \max}$	467.6	mm	-
	d	360	mm	-
	$d_{2G}$	Tr380x5		-
	$d_{a \min}$	372.4	mm	-
	$d_s$	9.5	mm	-
	l	112	mm	-
	$n_s$	17.7	mm	-
	$r_{a \max}$	2.5	mm	-
	$r_{\min}$	3	mm	-
说明		AH3972G		型号, 退卸套
重量	m	45000	g	质量
	$m_1$	13000	g	质量, 退卸套
基本额定载荷	$C_r$	1430000	N	基本额定动载荷, 径向
计算系数	e	0.17		-
	$Y_1$	4.05		-
	$Y_2$	6.04		-
基本额定载荷	$C_{0r}$	3200000	N	基本额定静载荷, 径向
计算系数	$Y_0$	3.96		-
极限转速	$n_G$	1540	r/min	极限转速
参考转速	$n_B$	810	r/min	参考速度
疲劳极限载荷	$C_{ur}$	209000	N	疲劳极限载荷, 径向

FAG 23972-K-MB + AH3972G图片



参考资料:<http://www.sozhou.com/p/2420226e.html>