

**FAG 240/850-B-K30-MB参数**

尺寸	d	850	mm	-
	D	1220	mm	-
	B	365	mm	-
	D <sub>1</sub>	1092.9	mm	-
	D <sub>a max</sub>	1192	mm	-
	d <sub>a min</sub>	878	mm	-
	d <sub>s</sub>	12.5	mm	-
	n <sub>s</sub>	23.5	mm	-
	r <sub>a max</sub>	6	mm	-
	r <sub>min</sub>	7.5	mm	-
重量	m	1420000	g	质量
基本额定载荷	C <sub>r</sub>	12900000	N	基本额定动载荷，径向
参考转速	n <sub>B</sub>	174	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	2060000	N	疲劳极限载荷，径向
基本额定静载荷	C <sub>0r</sub>	32000000	N	基本额定静载荷，径向
计算系数	Y <sub>0</sub>	2.28		-
极限转速	n <sub>G</sub>	390	r/min	极限转速
计算系数	e	0.29		-
	Y <sub>1</sub>	2.33		-
	Y <sub>2</sub>	3.47		-

**FAG 240/850-B-K30-MB图片**





参考资料:<http://www.sozhou.com/p/24d1bc7d.html>