

FAG 24192-B-K30-MB + AH24192参数

尺寸	d_{1H}	440	mm	-	
	D	760	mm	-	
	B	300	mm	-	
	a	23	mm	-	
	b	32	mm	-	
	D_1	642.8	mm	-	
	$D_{a\ max}$	728	mm	-	
	d	460	mm	-	
	d_{2G}	Tr480x5		-	
	$d_{a\ min}$	492	mm	-	
	d_s	12.5	mm	-	
	l	332	mm	-	
	n_s	23.5	mm	-	
	$r_{a\ max}$	6	mm	-	
	r_{min}	7.5	mm	-	
	说明		AH24192		型号, 退卸套
	重量	m	578000	g	质量
m_1		48700	g	质量, 退卸套	
基本额定载荷	C_r	7500000	N	基本额定动载荷, 径向	
计算系数	e	0.39		-	
	Y_1	1.73		-	
	Y_2	2.58		-	
基本额定载荷	C_{0r}	15600000	N	基本额定静载荷, 径向	
计算系数	Y_0	1.69		-	
极限转速	n_G	650	r/min	极限转速	
参考转速	n_B	228	r/min	参考速度	
疲劳极限载荷	C_{ur}	1160000	N	疲劳极限载荷, 径向	

FAG 24192-B-K30-MB + AH24192图片



参考资料:<http://www.sozhou.com/p/25b1739c.html>