

FAG 24160-B-K30 + AH24160参数

疲劳极限载荷	C_{ur}	530000	N	疲劳极限载荷，径向	
尺寸	d_{1H}	280	mm	-	
	D	500	mm	-	
	B	200	mm	-	
	a	18	mm	-	
	b	24	mm	-	
	D_1	424.4	mm	-	
	$D_{a\ max}$	480	mm	-	
	d	300	mm	-	
	d_{2G}	Tr320x5		-	
	$d_{a\ min}$	320	mm	-	
	d_s	8	mm	-	
	l	224	mm	-	
	n_s	15	mm	-	
	$r_{a\ max}$	4	mm	-	
	r_{min}	5	mm	-	
	说明		AH24160		型号，退卸套
	重量	m	158000	g	质量
m_1		20100	g	质量，退卸套	
基本额定载荷	C_r	3250000	N	基本额定动载荷，径向	
计算系数	e	0.4		-	
	Y_1	1.67		-	
	Y_2	2.49		-	
基本额定载荷	C_{0r}	6300000	N	基本额定静载荷，径向	
计算系数	Y_0	1.63		-	
极限转速	n_G	1100	r/min	极限转速	
参考转速	n_B	460	r/min	参考速度	

FAG 24160-B-K30 + AH24160图片



参考资料:<http://www.sozhou.com/p/29f35c91.html>