

FAG 30302-A参数

疲劳极限载荷	C_{ur}	2110	N	疲劳极限载荷，径向
极限转速	n_G	19800	r/min	极限转速
参考转速	n_B	12500	r/min	参考速度
说明		T2FB015		根据 DIN ISO 355 的 对应型号
尺寸	D	42	mm	-
	T	14.25	mm	-
	a	10	mm	-
	B	13	mm	-
	C	11	mm	-
	$C_{a \min}$	2	mm	-
	$C_{b \min}$	3	mm	-
	$D_{a \max}$	36	mm	-
	$D_{a \min}$	36	mm	-
	$D_{b \min}$	38	mm	-
	d_1	28.2	mm	-
	$d_{a \max}$	22	mm	-
	$d_{b \min}$	21	mm	-
	$r_{1, 2 \min}$	1	mm	-
	$r_{3, 4 \min}$	1	mm	-
	$r_{a \max}$	1	mm	-
	$r_{b \max}$	1	mm	-
重量	m	96	g	质量
基本额定载荷	C_r	23000	N	基本额定动载荷，径向
	C_{0r}	20500	N	基本额定静载荷，径向
计算系数	e	0.29		-
	Y	2.11		-
	Y_0	1.16		-

FAG 30302-A图片

