

FAG 32211-A参数

尺寸	$D_b \text{ min}$	95	mm	-	
	d_1	76.2	mm	-	
	$d_a \text{ max}$	63	mm	-	
	$d_b \text{ min}$	64	mm	-	
	$r_{1, 2} \text{ min}$	2	mm	-	
	$r_{3, 4} \text{ min}$	1.5	mm	-	
	$r_a \text{ max}$	2	mm	-	
	d	55	mm	-	
	D	100	mm	-	
	T	26.75	mm	-	
	a	23	mm	-	
	B	25	mm	-	
	C	21	mm	-	
	$C_a \text{ min}$	4	mm	-	
	$C_b \text{ min}$	5.5	mm	-	
	$D_a \text{ max}$	91	mm	-	
	$D_a \text{ min}$	87	mm	-	
	$r_b \text{ max}$	1.5	mm	-	
	重量	m	870	g	质量
	基本额定载荷	C_r	109000	N	基本额定动载荷, 径向
C_{0r}		135000	N	基本额定静载荷, 径向	
计算系数	e	0.4		-	
	Y	1.48		-	
	Y_0	0.81		-	
疲劳极限载荷	C_{ur}	16200	N	疲劳极限载荷, 径向	
极限转速	n_G	7200	r/min	极限转速	
参考转速	n_B	4050	r/min	参考速度	

FAG 32211-A图片

