

FAG 33024参数

尺寸	d	120	mm	-	
	D	180	mm	-	
	T	48	mm	-	
	a	36	mm	-	
	B	48	mm	-	
	C	38	mm	-	
	C <sub>a min</sub>	6	mm	-	
	C <sub>b min</sub>	10	mm	-	
	D <sub>a max</sub>	170	mm	-	
	D <sub>a min</sub>	160	mm	-	
	D <sub>b min</sub>	171	mm	-	
	d <sub>1</sub>	148.5	mm	-	
	d <sub>a max</sub>	132	mm	-	
	d <sub>b min</sub>	130	mm	-	
	r <sub>1, 2 min</sub>	2.5	mm	-	
	r <sub>3, 4 min</sub>	2	mm	-	
	r <sub>a max</sub>	2.5	mm	-	
	r <sub>b max</sub>	2	mm	-	
	重量	m	4550	g	质量
	基本额定载荷	C <sub>r</sub>	310000	N	基本额定动载荷, 径向
C <sub>0r</sub>		560000	N	基本额定静载荷, 径向	
计算系数	e	0.31		-	
	Y	1.97		-	
	Y <sub>0</sub>	1.08		-	
疲劳极限载荷	C <sub>ur</sub>	65000	N	疲劳极限载荷, 径向	
极限转速	n <sub>G</sub>	3700	r/min	极限转速	
参考转速	n <sub>B</sub>	2600	r/min	参考速度	

FAG 33024图片

