

FAG 7312-B-TVP参数

| | | | | |
|--------|---------------|-------|-------|------------|
| 尺寸 | $D_{a \max}$ | 118 | mm | - |
| | $D_{b \max}$ | 123 | mm | - |
| | d_1 | 87.3 | mm | - |
| | $d_{a \min}$ | 72 | mm | - |
| | $r_{1 \min}$ | 1.1 | mm | - |
| | $r_{a \max}$ | 2.1 | mm | - |
| | $r_{al \max}$ | 1 | mm | - |
| | r_{\min} | 2.1 | mm | - |
| 重量 | m | 1710 | g | 质量 |
| 基本额定载荷 | C_r | 96000 | N | 基本额定动载荷，径向 |
| 计算系数 | e | 1.14 | | - |
| | X | 0.35 | | - |
| | Y | 0.57 | | - |
| | Y_0 | 0.26 | | - |
| 基本额定载荷 | C_{0r} | 69000 | N | 基本额定静载荷，径向 |
| 极限转速 | n_G | 6400 | r/min | 极限转速 |
| 参考转速 | n_B | 5300 | r/min | 参考速度 |
| 疲劳极限载荷 | C_{ur} | 4650 | N | 疲劳极限载荷，径向 |
| 尺寸 | d | 60 | mm | - |
| | D | 130 | mm | - |
| | B | 31 | mm | - |
| | a | 55 | mm | - |
| | D_1 | 103.4 | mm | - |

FAG 7312-B-TVP图片



参考资料: <http://www.sozhou.com/p/354ec198.html>