

## FAG 30218-A参数

尺寸	d	90	mm	-	
	D	160	mm	-	
	T	32.5	mm	-	
	a	32	mm	-	
	B	30	mm	-	
	C	26	mm	-	
	C <sub>a min</sub>	5	mm	-	
	C <sub>b min</sub>	6.5	mm	-	
	D <sub>a max</sub>	150	mm	-	
	D <sub>a min</sub>	140	mm	-	
	D <sub>b min</sub>	150	mm	-	
	d <sub>1</sub>	121.3	mm	-	
	d <sub>a max</sub>	103	mm	-	
	d <sub>b min</sub>	100	mm	-	
	r <sub>1, 2 min</sub>	2.5	mm	-	
	r <sub>3, 4 min</sub>	2	mm	-	
	r <sub>a max</sub>	2.5	mm	-	
	r <sub>b max</sub>	2	mm	-	
	重量	m	2610	g	质量
	基本额定载荷	C <sub>r</sub>	201000	N	基本额定动载荷, 径向
C <sub>0r</sub>		255000	N	基本额定静载荷, 径向	
计算系数	e	0.42		-	
	Y	1.43		-	
	Y <sub>0</sub>	0.79		-	
疲劳极限载荷	C <sub>ur</sub>	29000	N	疲劳极限载荷, 径向	
极限转速	n <sub>G</sub>	4550	r/min	极限转速	
参考转速	n <sub>B</sub>	3050	r/min	参考速度	

FAG 30218-A图片

