

FAG 23124-E1-K-TVPB + AHX3124参数

尺寸	d_{1H}	115	mm	-	
	D	200	mm	-	
	B	62	mm	-	
	a	4	mm	-	
	b	12	mm	-	
	D_1	177.4	mm	-	
	$D_{a\ max}$	189	mm	-	
	d	120	mm	-	
	d_2	136.2	mm	-	
	d_{2G}	M130x2		-	
	$d_{a\ min}$	131	mm	-	
	d_s	4.8	mm	-	
	l	75	mm	-	
	n_s	9.5	mm	-	
	$r_{a\ max}$	2	mm	-	
	r_{min}	2	mm	-	
	说明		AHX3124		型号, 退卸套
	重量	m	7060	g	质量
		m_1	970	g	质量, 退卸套
	基本额定载荷	C_r	630000	N	基本额定动载荷, 径向
计算系数	e	0.28		-	
	Y_1	2.39		-	
	Y_2	3.56		-	
基本额定载荷	C_{0r}	800000	N	基本额定静载荷, 径向	
计算系数	Y_0	2.34		-	
极限转速	n_G	3400	r/min	极限转速	
参考转速	n_B	2330	r/min	参考速度	
疲劳极限载荷	C_{ur}	73000	N	疲劳极限载荷, 径向	

FAG 23124-E1-K-TVPB + AHX3124图片



参考资料:<http://www.sozhou.com/p/41903264.html>