

## NSK CRBE-22参数

|         |        |         |       |        |
|---------|--------|---------|-------|--------|
| 型号      | 型号     | CRBE-22 |       | -      |
| 外形尺寸    | D      | 34.925  | mm    | 外径     |
|         | C      | 19.05   | mm    | 宽度     |
|         | SD     | 12.700  | mm    | 外径     |
| 尺寸      | G      | 1/2-20  | mm    | 螺栓     |
|         | G1     | 15.9    | mm    | -      |
|         | B1     | 52.2    | mm    | -      |
|         | B2     | 31.75   | mm    | -      |
|         | B3     | 7.94    | mm    | -      |
|         | M2     | 3.2     | mm    | -      |
|         | M1     | 4.8     | mm    | -      |
|         | 基本额定载荷 | CR      | 18500 | N      |
| CR2     |        | 1890    | kgf   | 动载荷    |
| 极限载荷    | PMAX   | 9600    | N     | 极限载荷   |
|         | PMAX2  | 975     | kgf   | 极限载荷   |
| 滚轮极限载荷  | LTL    | 11500   | N     | 滚轮极限载荷 |
| 重量      | MASS   | 160     | g     | 重量     |
| 六角形孔的尺寸 | X      | 6.35    | mm    | 双边距离   |
| 偏心轴衬尺寸  | B4     | 15.88   | mm    | -      |
|         | SD1    | 17.450  | mm    | -      |
|         | E      | 0.76    | mm    | -      |
| 挡肩尺寸    | F      | 19.0    | mm    | (最小)   |
| 拧紧力矩    | TT     | 2310    | n. cm | (最大)   |

## NSK CRBE-22图片





CRE

参考资料:<http://www.sozhou.com/p/4203399e.html>

