

FAG 24068-B-K30-MB + AH24068参数

尺寸	$d_{1H}$	320	mm	-
	D	520	mm	-
	B	180	mm	-
	a	19	mm	-
	b	26	mm	-
	$D_1$	457.1	mm	-
	$D_{a\ max}$	502	mm	-
	d	340	mm	-
	$d_{2G}$	Tr360x5		-
	$d_{a\ min}$	358	mm	-
	$d_s$	9.5	mm	-
	l	206	mm	-
	$n_s$	17.7	mm	-
	$r_{a\ max}$	4	mm	-
	$r_{min}$	5	mm	-
	说明		AH24068	
重量	m	143000	g	质量
	$m_1$	21100	g	质量, 退卸套
基本额定载荷	$C_r$	3100000	N	基本额定动载荷, 径向
计算系数	e	0.34		-
	$Y_1$	1.98		-
	$Y_2$	2.94		-
基本额定载荷	$C_{0r}$	6550000	N	基本额定静载荷, 径向
计算系数	$Y_0$	1.93		-
极限转速	$n_G$	1080	r/min	极限转速
参考转速	$n_B$	600	r/min	参考速度
疲劳极限载荷	$C_{ur}$	530000	N	疲劳极限载荷, 径向

FAG 24068-B-K30-MB + AH24068图片



参考资料:<http://www.sozhou.com/p/42da9b63.html>