

NSK CRSBE-44参数

| | | | | |
|---------|-------|----------|-------|--------|
| 滚轮极限载荷 | LTL | 45500 | N | 滚轮极限载荷 |
| 重量 | MASS | 1350 | g | 重量 |
| 六角形孔的尺寸 | X | 12.70 | mm | 双边距离 |
| 偏心轴衬尺寸 | B4 | 28.58 | mm | - |
| | SD1 | 34.925 | mm | - |
| | E | 0.76 | mm | - |
| 挡肩尺寸 | F | 34.9 | mm | (最小) |
| 拧紧力矩 | TT | 15300 | n. cm | (最大) |
| 型号 | 型号 | CRSBE-44 | | - |
| 外形尺寸 | D | 69.850 | mm | 外径 |
| | C | 38.10 | mm | 宽度 |
| | SD | 25.400 | mm | 外径 |
| 尺寸 | G | 1-14 | mm | 螺栓 |
| | G1 | 28.6 | mm | - |
| | B1 | 96.9 | mm | - |
| | B2 | 57.15 | mm | - |
| | B3 | 14.29 | mm | - |
| | M2 | 4.8 | mm | - |
| | M1 | 4.8 | mm | - |
| 基本额定载荷 | CR | 52500 | N | 动载荷 |
| | CR2 | 5350 | kgf | 动载荷 |
| 极限载荷 | PMAX | 43000 | N | 极限载荷 |
| | PMAX2 | 4400 | kgf | 极限载荷 |

NSK CRSBE-44图片





CRE

参考资料:<http://www.sozhou.com/p/441bdaf1.html>

