

## FAG NU1005-M1 参数

尺寸	d	25	mm	-
	D	47	mm	-
	B	12	mm	-
	D <sub>1</sub>	39.3	mm	-
	D <sub>a max</sub>	44	mm	-
	d <sub>a max</sub>	30	mm	-
	d <sub>a min</sub>	27	mm	-
	d <sub>b min</sub>	32	mm	-
	E	41.5	mm	-
	F	30.5	mm	-
	r <sub>1 min</sub>	0.3	mm	-
	r <sub>a max</sub>	0.6	mm	-
	r <sub>al max</sub>	0.3	mm	-
	r <sub>min</sub>	0.6	mm	-
	s	2.4	mm	距离中心位置的轴向偏移
重量	m	92	g	质量
基本额定载荷	C <sub>r</sub>	18500	N	基本额定动载荷，径向
	C <sub>0r</sub>	14800	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	26000	r/min	极限转速
参考转速	n <sub>B</sub>	12900	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	1780	N	疲劳极限载荷，径向

## FAG NU1005-M1 图片



参考资料:<http://www.sozhou.com/p/4d50585f.html>

