

FAG 239/900-K-MB + AH39/900参数

尺寸	$d_{1H}$	850	mm	-
	D	1180	mm	-
	B	206	mm	-
	a	12	mm	-
	b	51	mm	-
	$D_1$	1098.8	mm	-
	$D_{a \max}$	1157	mm	-
	d	900	mm	-
	$d_{2G}$	Tr930x8		-
	$d_{a \min}$	923	mm	-
	$d_s$	12.5	mm	-
	l	265	mm	-
	$n_s$	23.5	mm	-
	$r_{a \max}$	5	mm	-
	$r_{\min}$	6	mm	-
说明		AH39/900		型号, 退卸套
重量	m	641000	g	质量
	$m_1$	180000	g	质量, 退卸套
基本额定载荷	$C_r$	6550000	N	基本额定动载荷, 径向
计算系数	e	0.16		-
	$Y_1$	4.28		-
	$Y_2$	6.37		-
基本额定载荷	$C_{0r}$	17300000	N	基本额定静载荷, 径向
计算系数	$Y_0$	4.19		-
极限转速	$n_G$	520	r/min	极限转速
参考转速	$n_B$	260	r/min	参考速度
疲劳极限载荷	$C_{ur}$	1010000	N	疲劳极限载荷, 径向

FAG 239/900-K-MB + AH39/900图片



参考资料:<http://www.sozhou.com/p/4f77011e.html>