

FAG 23956-K-MB + AH3956G参数

尺寸	B	75	mm	-
	a	6	mm	-
	b	18	mm	-
	D <sub>1</sub>	350	mm	-
	D <sub>a max</sub>	369.8	mm	-
	d	280	mm	-
	d <sub>2G</sub>	Tr300x4		-
	d <sub>a min</sub>	290.2	mm	-
	d <sub>s</sub>	8	mm	-
	l	94	mm	-
	n <sub>s</sub>	15	mm	-
	r <sub>a max</sub>	2.1	mm	-
	r <sub>min</sub>	2.1	mm	-
说明		AH3956G		型号, 退卸套
重量	m	24700	g	质量
	m <sub>1</sub>	8300	g	质量, 退卸套
基本额定载荷	C <sub>r</sub>	970000	N	基本额定动载荷, 径向
计算系数	e	0.18		-
	Y <sub>1</sub>	3.76		-
	Y <sub>2</sub>	5.59		-
基本额定载荷	C <sub>0r</sub>	2040000	N	基本额定静载荷, 径向
计算系数	Y <sub>0</sub>	3.67		-
极限转速	n <sub>G</sub>	2000	r/min	极限转速
参考转速	n <sub>B</sub>	1100	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	129000	N	疲劳极限载荷, 径向
尺寸	d <sub>1H</sub>	260	mm	-
	D	380	mm	-

FAG 23956-K-MB + AH3956G图片



参考资料:<http://www.sozhou.com/p/517c5488.html>