

TIMKEN 16582/16522参数

轴承类型	Bearing Type	TRB		-
子类	Bearing Subtype	TS		-
尺寸	Cone (Inner)	16582		内圈
	Cup (Outer)	16522		外圈
额定载荷	d	33.3375	mm	内径
	D	68.2625	mm	外径
	T	22.225	mm	宽度
	C1	66723.3	N	一百万转动态径向载荷
	C90	17303.6	N	九千万转动态径向载荷
	Ca90	8140.25	N	九千万转单列轴承动态轴向载荷
	C0	77843.9	N	静态额定载荷
尺寸	$K = 0.39 / \tan$ (contact angle)	2.12		系数
	$e = 1.5 * \tan$ (contact angle)	0.28		系数
	$Y = 0.4 / \tan$ (contact angle)	2.18		系数
几何结构系数	Cg	0.0650		几何系数
尺寸	B	22.225	mm	内圈宽度
	R	1.524	mm	最大轴肩倒角半径
	db	40.894	mm	轴肩直径
	da	38.608	mm	轴肩直径
	Aa	0.762	mm	保持架（负值表示保持架超出内圈大端面）
	Ab	1.524	mm	保持架（负值表示保持架没超出内圈小端面）
	C	17.4625	mm	外圈宽度
	r	0.762	mm	最大轴承座挡肩圆角半径
	Db	60.96	mm	轴承座挡肩直径
	Da	62.992	mm	轴承座挡肩直径
	a	-7.366	mm	有效中心位置
重量	Assembly Weight	371.95	g	-

TIMKEN 16582/16522图片







参考资料:<http://www.sozhou.com/p/5691a614.html>

