

NSK CRE-16参数

| | | | | |
|---------|--------|---------|-------|--------|
| 型号 | 型号 | CRE-16 | | - |
| 外形尺寸 | D | 25.400 | mm | 外径 |
| | C | 15.88 | mm | 宽度 |
| | SD | 11.112 | mm | 外径 |
| 尺寸 | G | 7/16-20 | mm | 螺栓 |
| | G1 | 12.7 | mm | - |
| | B1 | 42.4 | mm | - |
| | B2 | 25.40 | mm | - |
| | B3 | 6.35 | mm | - |
| | M2 | 3.2 | mm | - |
| | M1 | 4.8 | mm | - |
| | 基本额定载荷 | CR | 11200 | N |
| CR2 | | 1140 | kgf | 动载荷 |
| 极限载荷 | PMAX | 6950 | N | 极限载荷 |
| | PMAX2 | 710 | kgf | 极限载荷 |
| 滚轮极限载荷 | LTL | 6550 | N | 滚轮极限载荷 |
| 重量 | MASS | 73 | g | 重量 |
| 六角形孔的尺寸 | X | 0.00 | mm | 双边距离 |
| 偏心轴衬尺寸 | B4 | 12.70 | mm | - |
| | SD1 | 15.875 | mm | - |
| | E | 0.76 | mm | - |
| 挡肩尺寸 | F | 15.1 | mm | (最小) |
| 拧紧力矩 | TT | 1700 | n. cm | (最大) |

NSK CRE-16图片





CRE

参考资料:<http://www.sozhou.com/p/5842fd0a.html>

