

## FAG 33206参数

说明	T2DE030			根据 DIN ISO 355 的 对应型号
尺寸	$D_{a \max}$	56	mm	-
	$D_{a \min}$	53	mm	-
	$D_{b \min}$	59	mm	-
	$d_1$	46.1	mm	-
	$d_{a \max}$	36	mm	-
	$d_{b \min}$	36	mm	-
	$r_{1, 2 \min}$	1	mm	-
	$r_{3, 4 \min}$	1	mm	-
	$r_{a \max}$	1	mm	-
	$r_{b \max}$	1	mm	-
重量	m	394	g	质量
基本额定载荷	$C_r$	65000	N	基本额定动载荷，径向
	$C_{0r}$	77000	N	基本额定静载荷，径向
计算系数	e	0.34		-
	Y	1.76		-
	$Y_0$	0.97		-
疲劳极限载荷	$C_{ur}$	9400	N	疲劳极限载荷，径向
极限转速	$n_G$	11800	r/min	极限转速
参考转速	$n_B$	7100	r/min	参考速度
尺寸	d	30	mm	-
	D	62	mm	-
	T	25	mm	-
	a	16	mm	-
	B	25	mm	-
	C	19.5	mm	-
	$C_{a \min}$	5	mm	-

## FAG 33206图片

