

### FAG 294/950-E-MB参数

尺寸	d	950	mm	-
	D	1600	mm	-
	T	390	mm	-
	A	546	mm	-
	D <sub>1</sub>	1211	mm	-
	D <sub>a max</sub>	1241	mm	-
	D <sub>b min</sub>	1635	mm	-
	d <sub>1</sub>	1470	mm	-
	d <sub>a min</sub>	1372	mm	-
	d <sub>b max</sub>	1022	mm	-
	r <sub>a max</sub>	15	mm	-
	r <sub>min</sub>	15	mm	-
	T <sub>1</sub>	188	mm	-
	T <sub>2</sub>	140	mm	-
	T <sub>3</sub>	256	mm	-
	T <sub>4</sub>	290	mm	-
	重量	m	3019700	g
基本额定载荷	C <sub>a</sub>	27500000	N	基本额定动载荷, 轴向
	C <sub>0a</sub>	128000000	N	基本额定静载荷, 轴向
极限转速	n <sub>G</sub>	290	r/min	极限转速
参考转速	n <sub>B</sub>	159	r/min	参考速度
疲劳极限载荷	C <sub>ua</sub>	0	N	疲劳极限载荷, 轴向

### FAG 294/950-E-MB图片



参考资料:<http://www.sozhou.com/p/61fd4e3e.html>