

FAG 33010参数

尺寸	d	50	mm	-	
	D	80	mm	-	
	T	24	mm	-	
	a	17	mm	-	
	B	24	mm	-	
	C	19	mm	-	
	$C_a \text{ min}$	4	mm	-	
	$C_b \text{ min}$	5	mm	-	
	$D_a \text{ max}$	74	mm	-	
	$D_a \text{ min}$	72	mm	-	
	$D_b \text{ min}$	76	mm	-	
	d_1	65.8	mm	-	
	$d_a \text{ max}$	56	mm	-	
	$d_b \text{ min}$	56	mm	-	
	$r_{1, 2 \text{ min}}$	1	mm	-	
	$r_{3, 4 \text{ min}}$	1	mm	-	
	$r_a \text{ max}$	1	mm	-	
	$r_b \text{ max}$	1	mm	-	
	重量	m	470	g	质量
	基本额定载荷	C_r	75000	N	基本额定动载荷，径向
C_{0r}		113000	N	基本额定静载荷，径向	
计算系数	e	0.32		-	
	Y	1.9		-	
	Y_0	1.04		-	
疲劳极限载荷	C_{ur}	13900	N	疲劳极限载荷，径向	
极限转速	n_G	8700	r/min	极限转速	
参考转速	n_B	5400	r/min	参考速度	

FAG 33010图片

