

FAG NN3036-AS-K-M-SP参数

|        |               |         |       |             |
|--------|---------------|---------|-------|-------------|
| 尺寸     | d             | 180     | mm    | -           |
|        | D             | 280     | mm    | -           |
|        | B             | 74      | mm    | -           |
|        | $D_{a\ max}$  | 270     | mm    | -           |
|        | $D_{b\ min}$  | 258     | mm    | -           |
|        | $d_1$         | 218.2   | mm    | -           |
|        | $d_{a\ min}$  | 190     | mm    | -           |
|        | $d_s$         | 6.3     | mm    | -           |
|        | E             | 255     | mm    | -           |
|        | $n_s$         | 12.2    | mm    | -           |
|        | $r_{a\ max}$  | 2.1     | mm    | -           |
|        | $r_{min}$     | 2.1     | mm    | -           |
|        | s             | 4.8     | mm    | 距离中心位置的轴向偏移 |
|        | 重量            | m       | 16400 | g           |
| 基本额定载荷 | $C_r$         | 570000  | N     | 基本额定动载荷，径向  |
|        | $C_{0r}$      | 1000000 | N     | 基本额定静载荷，径向  |
| 极限转速   | $n_{G\ Fett}$ | 2800    | r/min | 脂润滑时的极限转速   |
|        | $n_{G\ Öl}$   | 3400    | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | $C_{ur}$      | 134000  | N     | 疲劳极限载荷，径向   |

FAG NN3036-AS-K-M-SP图片



