

FAG 239/710-K-MB + AH39/710参数

尺寸	d_{1H}	670	mm	-
	D	950	mm	-
	B	180	mm	-
	a	12	mm	-
	b	43	mm	-
	D_1	877.5	mm	-
	$D_{a \max}$	927	mm	-
	d	710	mm	-
	d_{2G}	Tr740x7		-
	$d_{a \min}$	733	mm	-
	d_s	12.5	mm	-
	l	228	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	5	mm	-
	r_{\min}	6	mm	-
说明		AH39/710		型号, 退卸套
重量	m	336000	g	质量
	m_1	101000	g	质量, 退卸套
基本额定载荷	C_r	4800000	N	基本额定动载荷, 径向
计算系数	e	0.18		-
	Y_1	3.85		-
	Y_2	5.73		-
基本额定载荷	C_{0r}	12000000	N	基本额定静载荷, 径向
计算系数	Y_0	3.76		-
极限转速	n_G	670	r/min	极限转速
参考转速	n_B	350	r/min	参考速度
疲劳极限载荷	C_{ur}	720000	N	疲劳极限载荷, 径向

FAG 239/710-K-MB + AH39/710图片



参考资料:<http://www.sozhou.com/p/6f16441a.html>