

FAG NJ2204-E-TVP2参数

尺寸	$r_{1 \text{ min}}$	0.6	mm	-
	$r_{a \text{ max}}$	1	mm	-
	$r_{al \text{ max}}$	0.6	mm	-
	r_{min}	1	mm	-
	s	1.8	mm	距离中心位置的轴向偏移
重量	m	150	g	质量
基本额定载荷	C_r	38500	N	基本额定动载荷，径向
	C_{0r}	31000	N	基本额定静载荷，径向
极限转速	n_G	19200	r/min	极限转速
参考转速	n_B	11400	r/min	参考速度
尺寸	d	20	mm	-
	$d_{a \text{ min}}$	24	mm	-
	$d_{c \text{ min}}$	32	mm	-
	F	26.5	mm	-
疲劳极限载荷	C_{ur}	5100	N	疲劳极限载荷，径向
尺寸	D	47	mm	-
	D_1	38.8	mm	-
	B	18	mm	-
	B_1	3	mm	-
	B_2	6.5	mm	-
	$D_{a \text{ max}}$	41	mm	-
	d_1	29.7	mm	-
	$d_{a \text{ max}}$	26	mm	-

FAG NJ2204-E-TVP2图片





参考资料:<http://www.sozhou.com/p/6f71b38c.html>