

FAG 23976-K-MB + AH3976G参数

基本额定载荷	C_r	1760000	N	基本额定动载荷，径向
计算系数	e	0.19		-
	Y_1	3.58		-
	Y_2	5.33		-
基本额定载荷	C_{0r}	4000000	N	基本额定静载荷，径向
计算系数	Y_0	3.5		-
极限转速	n_G	1340	r/min	极限转速
参考转速	n_B	760	r/min	参考速度
疲劳极限载荷	C_{ur}	265000	N	疲劳极限载荷，径向
尺寸	d_{1H}	360	mm	-
	D	520	mm	-
	B	106	mm	-
	a	8	mm	-
	b	22	mm	-
	D_1	477.6	mm	-
	$D_{a \max}$	505.4	mm	-
	d	380	mm	-
	d_{2G}	Tr400x5		-
	$d_{a \min}$	394.6	mm	-
	d_s	9.5	mm	-
	l	130	mm	-
	n_s	17.7	mm	-
	$r_{a \max}$	3	mm	-
	r_{\min}	4	mm	-
说明		AH3976G		型号，退卸套
重量	m	66300	g	质量
	m_1	16100	g	质量，退卸套

FAG 23976-K-MB + AH3976G图片



参考资料:<http://www.sozhou.com/p/701b2327.html>