

FAG 33210参数

极限转速	n_G	7700	r/min	极限转速
参考转速	n_B	4700	r/min	参考速度
说明		T3DE050		根据 DIN ISO 355 的 对应型号
尺寸	$D_{b \text{ min}}$	87	mm	-
	d_1	71.8	mm	-
	$d_{a \text{ max}}$	57	mm	-
	$d_{b \text{ min}}$	57	mm	-
	$r_{1, 2 \text{ min}}$	1.5	mm	-
	$r_{3, 4 \text{ min}}$	1.5	mm	-
	$r_{a \text{ max}}$	1.5	mm	-
	$r_{b \text{ max}}$	1.5	mm	-
重量	m	881	g	质量
基本额定载荷	C_r	115000	N	基本额定动载荷, 径向
	C_{0r}	163000	N	基本额定静载荷, 径向
计算系数	e	0.41		-
	Y	1.45		-
	Y_0	0.8		-
疲劳极限载荷	C_{ur}	20400	N	疲劳极限载荷, 径向
尺寸	a	24	mm	-
	B	32	mm	-
	C	24.5	mm	-
	$C_{a \text{ min}}$	5	mm	-
	$C_{b \text{ min}}$	7.5	mm	-
	$D_{a \text{ max}}$	83	mm	-
	$D_{a \text{ min}}$	77	mm	-
	d	50	mm	-
D	90	mm	-	

FAG 33210图片

