

### NSK 51232X参数

|      |        |        |        |      |
|------|--------|--------|--------|------|
| 极限转速 | GRE    | 900    | 1/min  | 脂润滑  |
|      | OIL    | 1400   | 1/min  | 油润滑  |
| 尺寸   | SD1    | 222    | mm     | -    |
|      | D1     | 163    | mm     | -    |
|      | D2     | 190    | mm     | -    |
|      | D3     | 235    | mm     | -    |
|      | SB     | 21.0   | mm     | -    |
|      | A      | 74.0   | mm     | -    |
|      | R      | 160    | mm     | -    |
|      | 安装尺寸   | SDA    | 199    | mm   |
| DA   |        | 186    | mm     | (最大) |
| SRA  |        | 1.5    | mm     | (最大) |
| 重量   | MASS   | 6040   | g      | 重量   |
| 型号   | 型号     | 51232X |        | -    |
| 外形尺寸 | SD     | 160    | mm     | 内径   |
|      | D      | 225    | mm     | 外径   |
|      | T      | 51     | mm     | 宽度   |
|      | T3     | 54.7   | mm     | -    |
|      | T4     | 61     | mm     | -    |
|      | SR     | 1.5    | mm     | (最小) |
|      | 基本额定载荷 | CAN    | 249000 | N    |
| COAN |        | 805000 | N      | 静载荷  |
| CA   |        | 25400  | kgf    | 动载荷  |
| COA  |        | 82000  | kgf    | 静载荷  |

### NSK 51232X图片



参考资料:<http://www.sozhou.com/p/72fd212f.html>

