

FAG HCB7212-C-T-P4S参数

| | | | | |
|--------|----------------------|-------|-------|-------------|
| 极限转速 | $n_{G \text{ Fett}}$ | 16000 | r/min | 脂润滑时的极限转速 |
| | $n_{G \text{ Öl}}$ | 26000 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | C_{ur} | 2260 | N | 疲劳极限载荷，径向 |
| 尺寸 | d | 60 | mm | - |
| | D | 110 | mm | - |
| | B | 22 | mm | - |
| | a | 23 | mm | - |
| | $D_a \text{ H12}$ | 101.5 | mm | - |
| | $d_a \text{ h12}$ | 69.5 | mm | - |
| | $r_{l \text{ min}}$ | 1.5 | mm | - |
| | $r_{a \text{ max}}$ | 1.5 | mm | - |
| | $r_{a1 \text{ max}}$ | 1.5 | mm | - |
| | r_{min} | 1.5 | mm | - |
| | 重量 | m | 687 | g |
| 基本额定载荷 | C_r | 56000 | N | 基本额定动载荷，径向 |
| | C_{0r} | 21700 | N | 基本额定静载荷，径向 |

FAG HCB7212-C-T-P4S图片



