


TIMKEN M88048-S/M88010参数

轴承类型	Bearing Type	TRB		-	
子类	Bearing Subtype	TS		-	
尺寸	Cone (Inner)	M88048-S		内圈	
	Cup (Outer)	M88010		外圈	
尺寸	d	33.3375	mm	内径	
	D	68.2625	mm	外径	
	T	22.225	mm	宽度	
	额定载荷	C1	76064.6	N	一百万转动态径向载荷
		C90	19794.6	N	九千万转动态径向载荷
		Ca90	18504.6	N	九千万转单列轴承动态轴向载荷
	C0	77399.1	N	静态额定载荷	
	$K = 0.39 / \tan$ (contact angle)	1.07		系数	
	$e = 1.5 * \tan$ (contact angle)	0.55		系数	
尺寸	$Y = 0.4 / \tan$ (contact angle)	1.10		系数	
几何结构系数	Cg	0.0771		几何系数	
尺寸	B	22.225	mm	内圈宽度	
	R	4.064	mm	最大轴肩倒角半径	
	db	49.53	mm	轴肩直径	
	da	41.148	mm	轴肩直径	
	Aa	1.524	mm	保持架（负值表示保持架超出内圈大端面）	
	Ab	1.016	mm	保持架（负值表示保持架没超出内圈小端面）	
	C	17.4625	mm	外圈宽度	
	r	1.524	mm	最大轴承座挡肩圆角半径	
	Db	57.912	mm	轴承座挡肩直径	
	Da	65.024	mm	轴承座挡肩直径	
	a	-2.794	mm	有效中心位置	
	重量	Assembly Weight	376.48	g	-

TIMKEN M88048-S/M88010图片







参考资料:<http://www.sozhou.com/p/7b20f103.html>

