

### FAG 7213-B-JP参数

尺寸	B	23	mm	-
	a	51	mm	-
	D <sub>1</sub>	98.9	mm	-
	D <sub>a max</sub>	111	mm	-
	D <sub>b max</sub>	114.4	mm	-
	d <sub>1</sub>	86.4	mm	-
	d <sub>a min</sub>	74	mm	-
	r <sub>1 min</sub>	1	mm	-
	r <sub>a max</sub>	1.5	mm	-
	r <sub>a1 max</sub>	1	mm	-
	r <sub>min</sub>	1.5	mm	-
重量	m	1080	g	质量
基本额定载荷	C <sub>r</sub>	67000	N	基本额定动载荷，径向
计算系数	e	1.14		-
	X	0.35		-
	Y	0.57		-
	Y <sub>0</sub>	0.26		-
基本额定载荷	C <sub>0r</sub>	55000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	6900	r/min	极限转速
参考转速	n <sub>B</sub>	5700	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	3700	N	疲劳极限载荷，径向
尺寸	d	65	mm	-
	D	120	mm	-

### FAG 7213-B-JP图片



参考资料: <http://www.sozhou.com/p/80583816.html>