

FAG 3213-BD-TVH参数

| | | | | | |
|--------|--------------|----------|-------|------------|-----|
| 尺寸 | d | 65 | mm | - | |
| | D | 120 | mm | - | |
| | B | 38.1 | mm | - | |
| | a | 70.646 | mm | - | |
| | D_1 | 106.6 | mm | - | |
| | $D_{a \max}$ | 111 | mm | - | |
| | d_1 | 87.7 | mm | - | |
| | $d_{a \min}$ | 74 | mm | - | |
| | $r_{a \max}$ | 1.5 | mm | - | |
| | r_{\min} | 1.5 | mm | - | |
| | 接触角 | α | 30 | | 接触角 |
| | 重量 | m | 1604 | g | 质量 |
| 基本额定载荷 | C_r | 86000 | N | 基本额定动载荷，径向 | |
| | C_{0r} | 77000 | N | 基本额定静载荷，径向 | |
| 疲劳极限载荷 | C_{ur} | 5200 | N | 疲劳极限载荷，径向 | |
| 极限转速 | n_G | 5700 | r/min | 极限转速 | |
| 参考转速 | n_B | 6100 | r/min | 参考速度 | |

FAG 3213-BD-TVH图片





参考资料: <http://www.sozhou.com/p/809ab0ff.html>