

FAG 32924参数

尺寸	d	120	mm	-	
	D	165	mm	-	
	T	29	mm	-	
	a	29	mm	-	
	B	29	mm	-	
	C	23	mm	-	
	$C_{a \min}$	6	mm	-	
	$C_{b \min}$	6	mm	-	
	$D_{a \max}$	158	mm	-	
	$D_{a \min}$	154	mm	-	
	$D_{b \min}$	160	mm	-	
	d_1	141	mm	-	
	$d_{a \max}$	128	mm	-	
	$d_{b \min}$	127	mm	-	
	$r_{1, 2 \min}$	1.5	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	1.5	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	1820	g	质量
	极限转速	n_G	4100	r/min	极限转速
参考转速	n_B	2370	r/min	参考速度	
说明		T2CC120		根据 DIN ISO 355 的 对应型号	
疲劳极限载荷	C_{ur}	34500	N	疲劳极限载荷，径向	
基本额定载荷	C_r	176000	N	基本额定动载荷，径向	
	C_{0r}	305000	N	基本额定静载荷，径向	
计算系数	e	0.35		-	
	Y	1.72		-	

FAG 32924图片

