

FAG 33016参数

尺寸	d	80	mm	-	
	D	125	mm	-	
	T	36	mm	-	
	a	26	mm	-	
	B	36	mm	-	
	C	29.5	mm	-	
	$C_{a \min}$	6	mm	-	
	$C_{b \min}$	6.5	mm	-	
	$D_{a \max}$	117	mm	-	
	$D_{a \min}$	112	mm	-	
	$D_{b \min}$	119	mm	-	
	d_1	102.6	mm	-	
	$d_{a \max}$	90	mm	-	
	$d_{b \min}$	87	mm	-	
	$r_{1, 2 \min}$	1.5	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	1.5	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	1670	g	质量
	基本额定载荷	C_r	175000	N	基本额定动载荷，径向
C_{0r}		290000	N	基本额定静载荷，径向	
计算系数	e	0.28		-	
	Y	2.16		-	
	Y_0	1.19		-	
疲劳极限载荷	C_{ur}	37000	N	疲劳极限载荷，径向	
极限转速	n_G	5400	r/min	极限转速	
参考转速	n_B	3600	r/min	参考速度	

FAG 33016图片

