


SKF BSD 45100 C参数

主要尺寸	d	45	mm	-
	D	100	mm	-
	H	20	mm	-
基本额定载荷	C	65500	N	动载荷
	C_0	183000	N	静载荷
疲劳载荷极限	P_u	6700	N	-
可达转速	Grease lubrication	5600	r/min	-
	Oil-air lubrication	6700	r/min	-
重量	重量	770	g	-
型号	型号	BSD 45100 C	-	-

SKF BSD 45100 C图片






	预载荷等级	
	A	B
Preload¹⁾ [N]	5850	11700
Frictional moment¹⁾ [Nm] (guideline value)	0,5	0,97
Static axial stiffness¹⁾ [N/μm] (guideline value)	1470	1870

Max. axial load carrying capacity (guideline value)	107,4
Reference grease quantity [cm³]	G _{ref} 5,9

¹⁾ Values apply to unmounted bearing set with two bearings arranged back-to-back or face-to-face

参考资料: <http://www.sozhou.com/p/8945a05e.html>



预载荷等级

	A	B
Preload¹⁾ [N]	5850	11700
Frictional moment¹⁾ [Nm] (guideline value)	0,5	0,97
Static axial stiffness¹⁾ [N/μm] (guideline value)	1470	1870

Max. axial load carrying capacity

(guideline value)
107,4

Reference grease quantity [cm³]

G_{ref} 5,9

Preload¹⁾ [N]

Frictional moment¹⁾ [Nm]

(guideline value)

Static axial stiffness¹⁾ [N/μm]

(guideline value)

¹⁾ Values apply to unmounted bearing set with two bearings arranged back-to-back or face-to-face