

NACHI N1014参数

| | | | | |
|-----------|--------|----------|-------|------|
| 外形尺寸 | d | 70 | mm | 内径 |
| | D | 110 | mm | 外径 |
| | B | 20 | mm | 宽度 |
| | r | 1.1~2 | mm | 轴向 |
| | r | 1.1~3.5 | mm | 轴向 |
| | r1 | 1~1.9 | mm | 径向 |
| | r1 | 1~3 | mm | 径向 |
| | Ew | 100 | mm | - |
| | 安装尺寸 | da (min) | 76.5 | mm |
| dc (min) | | 82 | mm | (最小) |
| Da (max) | | 103 | mm | (最大) |
| Db (max) | | 105 | mm | (最大) |
| Db (min) | | 100.5 | mm | (最小) |
| ra (max) | | 1 | mm | (最大) |
| ral (max) | | 1 | mm | (最大) |
| 重量 | Mass | 702 | g | 重量 |
| 基本额定载荷 | Cr | 58500 | N | 动载荷 |
| | Cor | 70500 | N | 静载荷 |
| 极限速度 | Grease | 6000 | r/min | 脂润滑 |
| | Oil | 7100 | r/min | 油润滑 |

NACHI N1014图片

参考资料:<http://www.sozhou.com/p/8c55e1e5.html>

