

**FAG B7044-E-T-P4S参数**

|          |                    |        |        |             |
|----------|--------------------|--------|--------|-------------|
| 尺寸       | d                  | 220    | mm     | -           |
|          | D                  | 340    | mm     | -           |
|          | B                  | 56     | mm     | -           |
|          | a                  | 93     | mm     | -           |
|          | $D_a$ H12          | 321    | mm     | -           |
|          | $d_a$ h12          | 239    | mm     | -           |
|          | $r_{1\ min}$       | 3      | mm     | -           |
|          | $r_{a\ max}$       | 2.5    | mm     | -           |
|          | $r_{al\ max}$      | 1      | mm     | -           |
|          | $r_{\min}$         | 3      | mm     | -           |
|          | 基本额定载荷             | $C_r$  | 315000 | N           |
| $C_{0r}$ |                    | 295000 | N      | 基本额定静载荷，径向  |
| 极限转速     | $n_{G\ Fett}$      | 3600   | r/min  | 脂润滑时的极限转速   |
|          | $n_{G\ \ddot{O}l}$ | 5300   | r/min  | 最少油润滑时的极限转速 |
| 疲劳极限载荷   | $C_{ur}$           | 18000  | N      | 疲劳极限载荷，径向   |
| 重量       | m                  | 15700  | g      | 质量          |

**FAG B7044-E-T-P4S图片**



