

## FAG 33015参数

尺寸	d	75	mm	-	
	D	115	mm	-	
	T	31	mm	-	
	a	23	mm	-	
	B	31	mm	-	
	C	25.5	mm	-	
	$C_{a \min}$	6	mm	-	
	$C_{b \min}$	5.5	mm	-	
	$D_{a \max}$	108	mm	-	
	$D_{a \min}$	104	mm	-	
	$D_{b \min}$	110	mm	-	
	$d_1$	96.4	mm	-	
	$d_{a \max}$	83	mm	-	
	$d_{b \min}$	82	mm	-	
	$r_{1, 2 \min}$	1.5	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	1.5	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	1160	g	质量
	基本额定载荷	$C_r$	139000	N	基本额定动载荷，径向
$C_{0r}$		232000	N	基本额定静载荷，径向	
计算系数	e	0.3		-	
疲劳极限载荷	$C_{ur}$	30000	N	疲劳极限载荷，径向	
极限转速	$n_G$	5900	r/min	极限转速	
参考转速	$n_B$	3700	r/min	参考速度	
说明		T2CE075		根据 DIN ISO 355 的 对应型号	
计算系数	Y	2.01		-	

