

FAG 32232-A参数

尺寸	d	160	mm	-	
	D	290	mm	-	
	T	84	mm	-	
	a	69	mm	-	
	B	80	mm	-	
	C	67	mm	-	
	$C_{a \text{ min}}$	10	mm	-	
	$C_{b \text{ min}}$	17	mm	-	
	$D_{a \text{ max}}$	276	mm	-	
	$D_{a \text{ min}}$	242	mm	-	
	$D_{b \text{ min}}$	274	mm	-	
	d_1	223	mm	-	
	$d_{a \text{ max}}$	183	mm	-	
	$d_{b \text{ min}}$	174	mm	-	
	$r_{3, 4 \text{ min}}$	3	mm	-	
	$r_{a \text{ max}}$	4	mm	-	
	$r_{b \text{ max}}$	3	mm	-	
	重量	m	23400	g	质量
	基本额定载荷	C_r	870000	N	基本额定动载荷, 径向
		C_{0r}	1380000	N	基本额定静载荷, 径向
计算系数	e	0.44		-	
	Y	1.38		-	
	Y_0	0.76		-	
疲劳极限载荷	C_{ur}	162000	N	疲劳极限载荷, 径向	
极限转速	n_G	2300	r/min	极限转速	
参考转速	n_B	1410	r/min	参考速度	
说明		T4GD160		根据 DIN ISO 355 的 对应型号	

FAG 32232-A图片

