

**FAG 23126-E1-TVPB参数**

尺寸	d	130	mm	-
	D	210	mm	-
	B	64	mm	-
	D <sub>1</sub>	187.3	mm	-
	D <sub>a max</sub>	199	mm	-
	d <sub>2</sub>	146	mm	-
	d <sub>a min</sub>	141	mm	-
	d <sub>s</sub>	4.8	mm	-
	n <sub>s</sub>	9.5	mm	-
	r <sub>a max</sub>	2	mm	-
	r <sub>min</sub>	2	mm	-
	重量	m	8110	g
基本额定载荷	C <sub>r</sub>	680000	N	基本额定动载荷，径向
计算系数	e	0.28		-
	Y <sub>1</sub>	2.45		-
	Y <sub>2</sub>	3.64		-
基本额定载荷	C <sub>0r</sub>	890000	N	基本额定静载荷，径向
计算系数	Y <sub>0</sub>	2.39		-
极限转速	n <sub>G</sub>	3200	r/min	极限转速
参考转速	n <sub>B</sub>	2140	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	79000	N	疲劳极限载荷，径向

**FAG 23126-E1-TVPB图片**



参考资料:<http://www.sozhou.com/p/9a6f2b1b.html>