

FAG NUP244-E-M1 参数

| | | | | |
|--------|---------------------|---------|-------|-------------|
| 尺寸 | d | 220 | mm | - |
| | D | 400 | mm | - |
| | B | 65 | mm | - |
| | B ₃ | 10 | mm | - |
| | D ₁ | 344.9 | mm | - |
| | D _{a max} | 383 | mm | - |
| | d ₁ | 285.2 | mm | - |
| | d _{a max} | 265 | mm | - |
| | d _{a min} | 237 | mm | - |
| | d _{c min} | 288 | mm | - |
| | F | 268 | mm | - |
| | r _{1 min} | 4 | mm | - |
| | r _{a max} | 3 | mm | - |
| | r _{al max} | 3 | mm | - |
| | r _{min} | 4 | mm | - |
| | s | 5.5 | mm | 距离中心位置的轴向偏移 |
| 重量 | m | 39300 | g | 质量 |
| 基本额定载荷 | C _r | 950000 | N | 基本额定动载荷，径向 |
| | C _{0r} | 1330000 | N | 基本额定静载荷，径向 |
| 极限转速 | n _G | 2600 | r/min | 极限转速 |
| 参考转速 | n _B | 1400 | r/min | 参考速度 |
| 疲劳极限载荷 | C _{ur} | 150000 | N | 疲劳极限载荷，径向 |

FAG NUP244-E-M1 图片



参考资料:<http://www.sozhou.com/p/9acd0868.html>

